



**Specification and General Notes:**

1. All jurisdiction-specific components SUPPLEMENTAL to MMCD PLATINUM fabricated in accordance with CSA CERTIFICATE OF QUALIFICATION (CSA A23.4-09).
2. Components certified to CSA standards (CSA A23.4-09) by approved independent third party certification body accredited by Standards Council of Canada.
3. All components marked with certification body logo and CSA standard markings.
4. Testing to CSA 23.1 & 2-09.
5. 30 MPa MIN compressive strength (MAX 0.5 W/C ratio).
6. Pipe penetrations to be grouted unless otherwise noted
7. 25mm MIN concrete cover of reinforcing steel.
8. 5mm manufacturing tolerance.
9. A-3 concrete exposure class.
10. 15MPa MIN stripping strength.
11. Standard grade form finish.
12. Unformed steel trowel or wood float finish.
13. Field installation and testing by others.

BILL OF MATERIALS			
ITEM	DESCRIPTION	MASS KG	QUANTITY
I	DMB6613	78	2

	<b>Description:</b> <b>Air Release Valve</b> L 4.7	Drawn : S.d. Approved :	Date : 18/01/2017 Load Rating: N/A	<b>Catalog No.</b>
	<b>Jurisdiction: Corporation of Delta</b>	Rev. No.	Scale : 1:16	<b>Dwg. No.</b> <b>Delta-1</b>
	<b>7520 Conrad Street Burnaby, B.C. V5A 2H7 Phone : 604-415-5181 Fax : 604-415-5185</b> <b>www: diamondprecast.com</b>	This drawing is the property of the Diamond Precast Concrete. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner		<b>Sheet No.</b> 1 OF 1