



**BILL OF MATERIALS**

ITEM	DESCRIPTION	MASS KG	QUANTITY
1	3036CBS	566	1
2	30DLROM	117	1
3	CBR		1 - 3
4	D26B-FRAME	35	1
5	D26B-GRATE	49	1

**Specification and General Notes:**

1. All components MMCD PLATINUM (Section 33 44 01) compliant and fabricated to CSA CERTIFICATE OF COMPLIANCE (ASTM C478M)
2. All jurisdiction-specific components SUPPLEMENTAL to MMCD PLATINUM fabricated in accordance with CSA CERTIFICATE OF QUALIFICATION (CSA A23.4-09).
3. Components certified to CSA standards (ASTM C478M & CSA A23.4-09) by approved independent third party certification body accredited by Standards Council of Canada.
4. All components marked with certification body logo and CSA standard markings.
5. Testing to ASTM C497/CSA 23.1 & 2-09.
6. 30 MPa MIN compressive strength (MAX 0.5 W/C ratio).
7. Pipe penetrations to be grouted unless otherwise noted
8. 25mm MIN concrete cover of reinforcing steel.
9. 5mm manufacturing tolerance.
10. A-3 concrete exposure class.
11. 15MPa MIN stripping strength.
12. Standard grade form finish.
13. Unformed steel trowel or wood float finish.
14. 3 point rigging to meet WORK SAFE BC OHS (Guideline 14/15) requirement.
15. Field installation and testing by others.

	<b>Description:</b> <p align="center"><b>Surface Inlet</b></p> <p align="center">L 6.8</p>	Drawn : S.d. Approved :	Date : 18/01/2017 Load Rating: H20	<b>Catalog No.</b>  <b>Dwg. No.</b> <b>Delta-6</b>
	<b>Jurisdiction: Corporation of Delta</b>	Rev. No.	Scale : 1:16	<b>Sheet No.</b> 1 OF 1
	<p>7520 Conrad Street Burnaby, B.C. V5A 2H7 Phone : 604-415-5181 Fax : 604-415-5185          www: diamondprecast.com</p>			